

V-TAC


Meaningful Innovation.

7.64kWh

Wall Mounting Battery

05 YEAR
WARRANTY

SLIM DESIGN INTELLIGENT BMS



V-TAC.EU | LED-EUROPE.PL

TUV NORD

CE RoHS

LISTING DETAILS

Model No: **VT-48160**
SKU Code: **11548**
EAN Code: **3800157697347**

MASTER BOX PACKAGING

Qty Per Pallet: **125 pcs per pallet**
Net Weight : **80kg**
Product Size : **830*600*111.5mm**

GENERAL DATA

Rated Capacity	Typical 161Ah - Minimum 158Ah
Rated Voltage	48V
Factory SOC	30~60%
Voltage at end of Discharge	42V
Charging mode (CC-CV)	MAX 54.75V
Internal Impedance	≤40mΩ
Standard Charge Current	32A
Limiting Current	20A
Standard Discharge	32A
Maximum Charge Current	100A
Maximum Discharge Current	100A
Operation Temperature Range	Charge: 0~55°C Discharge: -20~60°C
Storage Temperature Range	<12 months : -10~35°C < 3 months: -10~45°C <7 day : -20~65°C
Volumetric specific energy	140.2WH/L
Gravimetric specific energy	96WH/KG
Communication mode	RS485/CAN
Battery software version	V1.0
Maximum series number	Forbid
Maximum number of parallels	15PCS

**SUPER
SLIM
DESIGN**

